

# IMPEX COLOR s.r.l.

## PRODUCT DATA SHEET

### **BELLA PAINT TR 50**

**ECO COMPATIBLE WALL PAINT FOR OPAQUE INTERIORS - TRANSPIRANT - HIGH COVERING CAPACITY.**

**NON TOXIC - ODOURLESS – WITHOUT SOLVENTS - VOC 0**

Formulated with raw materials selected respecting the environment and the user:

- Binder emulsions with a low free monomer content and without APEO (alkylphenoethoxylates), titanium dioxide, quality extenders and selected carbonates.
- Volatile organic substances content VOC = 0. without free formaldehyde.

Featuring good whiteness, high coverage, resistance to abrasion and optimal transpirability. Particularly suitable for high quality interior painting.

#### **APPLICATION**

Brush, roller, or airless application.

Apply the paint in two or three thin coats, waiting at least 4 hours between each coat. Dry on the surface after about two hours at 20°C and 65% U.R.; maximum resistance after about 15 days.

Only apply on clean, dry bases, free of dust, bloom and separating agents. Check the absorption and consistency of the sub-floor on new supports and treat with a coat of CRIL FIX acrylic primer.

Check that old paint is fixed well on previously painted supports; if necessary, scrape, brush carefully and apply a coat of the most suitable fixer for the conditions of the base.

Supports with mould must be carefully brushed and tempered through the application of *ANTIMUFFA S.105* (S.105 ANTI-MOULD DISTEMPER).

#### **THECNICAL DATA**

Resistance factor to water vapour diffusion : Sd = < 0.2 m. (DIN 52615).

Yield : about 8 – 10 mq./lt. per coat.

Dilution : 40% first coat, 30% second coat, with drinking water.