

IMPEX COLOR s.r.l.

PRODUCT DATA SHEET

BIANCO PLUS

EMULSION WALL PAINT FOR INTERIORS

CHARACTERISTICS

Formulated with acrylic styrene emulsions, pigments and precious extenders, selected, micronised mineral load.

Opaque, with excellent whiteness and coating capacity, easy to brush on and spread. Finely dispersed, it is particularly suitable for airless spray application.

Contains no harmful substances for environment and for user, low VOC.

APPLICATION

Apply using brush, roller or airless spray. Apply paint in two or more thin coats, wait at least 4 hours between each coat. Surface dries after about 2 hours at 20°C and 65% RH.

Maximum resistance after about 15 days.

Apply only to clean, dry, dust-free, efflorescence-free, compact surfaces. Check absorption on new surfaces and the consistency of the undercoat and treat with coat of acrylic primer CRIL FIX.

On painted surfaces, make sure that old paint is well-secured, and scrape or brush away any detached parts. Apply suitable fixative depending on surface condition.

Supports affected by mould must be carefully brushed and treated using BONIFICANTE ANTIMUFFA s. 105. mould treatment

THECNICAL DATA

Appearance	: dense liquid.
Colour	: white.
Smell	: weak and characteristic.
Permeability to vapour	: Sd = < 0.2 m (standard DIN 52615).
Resistance to humid scrubbing	: < 1000 cycles (Scrub Test – standard DIN 53778).
Yield	: about 8 – 10 sq.m/lt per coat.
Dilution	: 40% for the first coat; 25% for the second coat, with clean water.
Minimum temperature of application	: + 5 °C.
Packaging	: 14 litres and 5 litres.
Storage	: over 1 year, protected against frost and excess heat.