

IMPEX COLOR s.r.l.

PRODUCT DATA SHEET

CRIL FIX

WATER BASED ACRYLIC FIXATIVE

COMPOSITION

CRIL FIX consists of a particular dispersion of alkali resistant acrylic resins which are highly compatible with inorganic binders such as lime and cement.

CHARACTERISTICS

- Specific weight: 1,050 Kg/l approx.
- Consumption: 30-50 g/m² per coat (0.03-0.05 l/m²) according to the absorption of the undersurface.
- Yield: about 25 m²/l.

USE

CRIL FIX is an insulator, fixative or stabilizer of a base before the application of a finishing product, either paint or wall covering from our ACRYLIC RANGE. As it is a water based product, it can be applied without danger to the health of the user on both interiors and exteriors.

DILUTION

CRIL FIX should be diluted with about 5-8 parts water and then applied with a brush or roller. Wait at least 16 hours before application of paint or covering.

WARNING

CRIL FIX should be applied at a minimum working temperature of + 5 °C.

SUPPLY

- 20 / 5 / 1 lt. tins.

STORAGE

Protect from the cold.

Stored in a suitable place in its original packing, the material will last for 1 year.

QUALITY

CRIL FIX undergoes continuous and accurate checking by our laboratories. The raw materials used are selected and checked carefully.

This information is based on present-day technical knowledge and our experience.

It is intended as a guide.

IMPEX COLOR s.r.l. reserve the right to make technical modifications without notice. Edition 3/96 .