

IMPEX COLOR s.r.l.

PRODUCT DATA SHEET

LUXOR SATINATO

ACRYLIC HYDRO-ENAMEL PAINT FOR WALLS

USE

High quality acrylic hydro-enamel gloss paint, with high resistance on exterior and interior surfaces. Made with alkali resistant acrylic polymers and precious pigment.

The paint is easy to apply, water-repellent, washable with all common detergents, coats well and is extremely white. It remains elastic and dirt-resistant over the years. It adheres well to various supports such as interior and exterior walls, concrete, fibre-cement, plasterboard and galvanised sheet metal.

It is especially suited to interior painting, it is washable and can be disinfected in schools, hospitals and public areas. It can be used as dust protection on concrete or plaster walls in computer rooms or in laboratories.

APPLICATION

Apply the product by brush, roller or airless spray after being correctly diluted, onto clean, dry, solid, suitable surfaces that have been prepared with a coat of WALL BASE 025 primer.

For best results and uniform colour, the support surface must be prepared carefully to guarantee uniform absorption.

THECNICAL DATA

Appearance	: Dense liquid.
Colour	: white or coloured.
Smell	: weak and characteristic.
Time to wait before applying second coat	: 4 hours.
Consumption	: second support; average yield 10-12 m ² ./lt./coat.
Dilution	: 10 – 20% with water.
Minimum temperature of application	: + 5 °C.
Storage	: over 1 year.