

PRODUCT DATA SHEET

MARMORINO VENEZIA

CHARACTERISTICS AND UTILIZATIONS

The **Marmorino Venezia** is a mixture of particular and selectioned dusts and marble grits with other mineral ingredients with prevalence lime and other different additives which facilitate and garante an excellent anchorage to the support.

It is the characteristic "Marmorino" already used some centuries ago in the villas and in the most important palaces, today proposed again by the IMPEX COLOR in the present version, using the ancient formulas, but made with moderm technics.

The **Marmorino Venezia** can be used both inside and outside: for its particular mineral composition, the **Marmorino Venezia** has a good resistance both to the humidity and to the moulds. It has an excellent perspiration, even if it has a sufficient waterproofness.

PREPARATION OF THE PRODUCT

Mix the **Marmorino Venezia** with about 45% of clear water, using a low speed mixer; let the mixture rest for 10 - 15 minutes at least.

APPLICATION

After treating carefully the bottoms, apply a first coat of material with a inox trowel, leaving a thickness of 1 mm about, and paying attention to spread uniformly and plane the product, without blurs, lines, surmounts etc.

After about 12 hours (according to the absorption and the environmental temperature), apply a second coat of **Marmorino Venezia** with the same previous proceeding. When the second coat starts to be dry, apply a third coat of **Marmorino Venezia** and when this coat starts to be little dry pass the surface with the inox trowel pressing the product gently. As the third coat dries, polish the surface pressing the product, until to obtaining the wished effect.

Further advice: during the summer season or with very absorbing plasters you should wet the walls before the application of the first and also the second coat to avoid the lines of the trowel. During the application of the first coat, and to put in evidence the grains of marble, pass with the sponge float before it dries.

Protect, in case of outside works, the wall for three days at least (particularly during the periods of high humidity). Never apply the product under direct sun.

The **Marmorino Venezia** has natural colours; it is the type of marble that gives the tone.

In interior walls, the **Marmorino Venezia** can be treated with our NATURAL WAX or IDROWAX to get brightness and protection.

In exteriors and interiors walls, to protect the surface and make it water repellent, you can apply after 24 hours, our SILATOP COAT HIDRO to be careful that the application must be from the bottom to the top.

THECNICAL DATA

Yield	: about 0,7 Kg/sq.m per coat.
Tins	: 18 Kg. and 5 Kg.
Specific Weight	: 1,1 about at 20°C.
Exsiccation	: 2 hours to the tonch, 24 hours in depth.