

# IMPEX COLOR s.r.l.

## PRODUCT DATA SHEET

# PRESTIGE FINITURA

### DESCRIPTION

Ornamental decorative painting based on water, for home walls, offices or retail stores. It gives a semi-opaque look with good washability, scrub resistance and colour fastness.

### UTILIZATIONS

Any interior flat surfaces.

### SUPPORT PREPARATION

Apply one or two coats of PRESTIGE FONDO, diluted first with water 20 to 30 %.  
For old and/or damaged walls apply first CRIL FIX diluted with clean water 1:3 / 1:4.

### APPLICATION PROCEDURE

**PRESTIGE** Finishing can be tinted with the colorants and mixed delicately before the application. Spread the product with a medium size paintbrush in crossed way, from the top of the wall working your way down.

Work between 1 to 5 mq. Once the material becomes tacky and humid, start to move **PRESTIGE** in any direction blending in the product.

Use PRESTIGE SPATULA to obtain the final effect.

### RECCOMENDED USES

Don't use this product at less than 5°C or more than 35°C temperatures.

Effect thinning slowly, adding water in small portions.

Equipment cleaning with hot water.

### CHARACTERISTICS AND TECHNICAL DATA

Spreading rate	: ~8-10 mq/l
Surface dry / 25 °C	: 2-3 hours to touch 1-2 days to dry
Planning time	: 5-15 minutes
Specific gravity	: 1040 ±10 g/l
Viscosity at packing(Brookfield,20°C)	: ~7000 mPa.s
Thinning information	: ready to use or max 5% water.
Use	: for internal use.