

IMPEX COLOR s.r.l.

PRODUCT DATA SHEET

SANI – DECOR 0,7 mm / 1 mm **SILOXANE-BASED FINE LIGHT PLASTER**

DESCRIPTION

Suitable for giving a traditional appearance to the finish on exteriors, it is weatherproof and has the special property of permeability to water vapour.

CHARACTERISTICS AND TECHNICAL DATA

Granulometry	: About 0,7 mm and 1 mm.
Drying time	: About 4 hours at the surface, complete drying after 12 - 24 hours.
Specific weight	: 1,850 gr./lt. at about 20°C
Viscosity	: Varies according to the period of storage.
Yield	: 0,7 mm = 1,5 – 2 Kg./mq. in 2 coats. 1 mm = 1,8 – 2 Kg./mq.
Application method	: With inox or plastic trowel.
Dilution	: Ready to use.
Colours	: From the chart and samples made from compatible pigments.
Application cycle	: Suitable supports are those with the properties specified above. On a bottom with normal absorption apply a coat of SILOXANE SILCOTEX-FIXATIVE W100; on a surface with high absorption apply one or two coats of SILOXANE-SILCOTEX FIXATIVE S40. Apply the plastic product and finish as for a normal light plaster.
Conservation	: Protect from frost and excessive heat.
Storage	: 6 / 8 months.
Packing	: 25 Kg. and 5 Kg.