

IMPEX COLOR s.r.l.

PRODUCT DATA SHEET

LA VELATURA

CHARACTERISTICS

Semi covering ornamental glazing.

UTILIZATIONS

Special semi covering glazing, opaque applicable by brush, cloth, blotter, little sponge float, etc which allows to get some chromatic and very ornamental effects on internal and external plasters finished at civilian or other well prepared wall supports.

The special composition the very opaque aspect and the characteristic to maintain unchanged the perspiration of the support, make it particularly adapted to the restoration of antique fronts, assuring a perfect resistance to the atmospheric agents.

APPLICATION

The product must be diluted with clean water at 100%.

ON PLASTER : Apply the product on the well dried plaster with a brush and then go on working with brush, cloth, blotter, little sponge float or other in compliance with the wished effect.

ON WASHABLE PAINT : Prepare carefully the support with white or coloured washable paint, after about 6 hours go on applying the product with the chosen method.

IMPORTANT

Please dilute the product only before using it and only the quantity you need. After diluting, it may last for 2 or 3 days, no longer.

TECHICAL DATA

Yield : 12-14 mq. for litre per coat accordly with the substrate absorbation.

Dilution : 100% with clean water.

Stickiness : gel product.

Packets : 2,5 lt and 5 lt.

Drying : about 6-8 h.

Conservations : minimum temperature + 5 °C maximum + 35 °C.