

IMPEX COLOR s.r.l.

PRODUCT DATA SHEET

IL VELLUTO - FINISH

DECORATIVE FINISH WITH A SILKY EFFECT FOR INTERIORS

USES

Special spatula finish that makes it possible to obtain highly decorative colour effects on interior smooth stucco plasters or other perfectly smooth, properly prepared supports.

The special nature of the pigments used makes it possible to obtain a finish with special light reflection and refraction characteristics, with a velvety effect.

APPLICATION

The product is ready-to-use and should not be diluted.

Apply two coats of IL VELLUTO – PRIMER of a colour similar to the selected finish using a short hair roller. After the primer has dried completely, apply a coat of IL VELLUTO – FINISH in a thin and uniform layer on an area of approx. 1 sq.m using a flat brush with soft bristles.

Smooth out the still wet surface with a stainless steel plastering trowel with rounded edges, removing any excess product. Keeping the plastering trowel still damp and clean, when the product begins to dry, work with a cross-hatch movement to obtain the chiaroscuro effect.

Continue using the same method for the next surface.

TECHNICAL DATA

Physical form	: dense liquid.
Colour	: neutral to be coloured with a tinting machine.
Odour	: characteristic weak.
Recoat ability	: after 4 hours.
Consumption	: depends on support – yield approx: 120 – 150 g/sq.m.
Storage	: beyond 1 year.
Minimum application temperature	: + 5° C.
Preservation	: keep away from extreme cold and excessive heat.

PREPARATION OF THE SUPPORTS

Apply only on perfectly smooth, dry and clean surfaces that are free of dust, efflorescences and release agents.

On already painted supports, make sure that the old paints are well anchored and scrape and brush carefully if necessary; crumbly surfaces should in any case be solidified with a highly penetrating fixative like CRILFIX and then smoothed. Supports contaminated by mould and mildew should be carefully brushed and treated by applying ANTIMOULD AGENT s. 105.

Any fillings, smoothing or restorations of the substrate should be perfectly aged.

All of the information, recommendations and suggestions on this sheet regarding product use, are based on tests and data which is considered reliable, however, it is the user's responsibility to determine if the products described herein are suitable for their specific use. Since actual use by others is beyond our control, no explicit or implicit guarantee is generally provided concerning the effects of such use or for the expected results nor shall we be held liable for use of the products described herein by others without not under our specific control. The information contained herein is not to be interpreted as absolutely complete, since additional information may be necessary or advised when particular or exceptional work conditions or circumstance exist. Our technical staff is available to provide more information and explanations to resolve specific problems.