

PRODUCT DATA SHEET

MARMORINO PASTA MEDIA

CHARACTERISTICS AND UTILIZATIONS

The **Marmorino Pasta Media** is a mixture of particular and selectioned dusts and marble grits with other mineral ingredients with prevalence lime and other different additives which facilitate and guarantee an excellent anchorage to the support.

It is the characteristic "Marmorino" already used some centuries ago in the villas and in the most important palaces, today proposed again by the IMPEX COLOR in the present version in past forme.

The **Marmorino Pasta Media** can be used both inside and outside: for its particular mineral composition, the **Marmorino Pasta Media** has a good resistance both to the humidity and to the moulds. It has an excellent perspiration, even if it has a sufficient waterproofness.

APPLICATION

After treating carefully the bottoms, apply a first coat of the material with an inox trowel, paying attention to spread uniformly and plane the product, without blurs, lines, surmounts etc.

After about 12 hours (according to the absorption and the environmental temperature), apply a second coat of **Marmorino Pasta Media** with the same previous proceeding, and before it begins to get dry, polish with the inox trowel making progressively more and more pressure.

This phase is important because it is in this moment that you succeed in compacting and polishing the **Marmorino Pasta Media**.

Further advice: during the summer season or with very absorbing plasters you should wet the walls before the application of the first and also the second coat to avoid the lines of the float, during the application of the first coat, and to put in evidence the grains of marble, pass with the sponge float before it dries.

Protect, in case of outside works, the wall for three days at least (particularly during the periods of high humidity).

The **Marmorino Pasta Media** has natural colours, it is the type of marble which gives a tone.

Inside the **Marmorino Pasta Media** can be treated with transparent wares to get brightness and protection.

In exteriors and interiors walls, to protect the surface and make it water repellent, you can apply after 24 hours, our SILATOP COAT HIDRO to be careful that the application must be from the bottom to the top.

THECNICAL DATA

Yield	: about 0,8 – 1 Kg/sq.m per coat.
Package	: 25 Kg. and 5 Kg.
Specific Weight	: 1,5 about at 20 °C.
Exsiccation	: 1 hour to the touch, 24 hours in depth.
Natural colours	: white.